

10/568463

14 FEB 2006
PCT/PTO

The present invention relates to a dispenser for air treatment agents, especially for use in deodorising or neutralising odours in an air space.

Air fresheners and other air treatment agents are widely used in many applications, in houses, vehicles and elsewhere. Although they are usually refillable, or cheap and disposable, it is inconvenient to have to fill or replace them often, particularly when many such items are in use for example in a large building. It is also an inconvenience to monitor levels within the devices in order to order refills or new stock as and when the devices become depleted. Furthermore, it can be wasteful to have such devices emitting when not needed.

It would therefore be desirable to extend the life of a substance to be dispensed in an air freshener or odour neutraliser, such as a fragrance for example, in order to reduce costs. One way of extending a life of an air freshener is to include a lid or closure substantially sealing the air freshener to prevent release of the active agents, until a user opens the lid. However, clearly this is inconvenient for the user, and again if a user forgets to re-close the lid after use, unwanted release of the active agents will continue until the device is depleted.

Automated versions of this idea have been proposed, in which a dispensing mechanism turns on and off periodically; set by a user. These systems are adequate when it is possible to predict when dispensing of the active agents is needed; but is inadequate if for example

malodour or other substances enter an atmosphere at non-regular intervals.

Efforts have been made to design an air freshener, which
5 dispenses fragrance, deodorant or sanitizing agent only
when a room is occupied, and which utilises infrared
detectors to detect movement within a room or air space.
However, it is rarely necessary to dispense the active
ingredient when a person is present in the room, unless
10 said person has undertaken activity, which produced
malodour or undesired odours. Thus infrared detection and
subsequent release of active ingredient can be relatively
wasteful, inefficient and expensive.

15 The need for efficient non-regular or regular release of
air freshener is equally applicable to other active
ingredients such as odour neutralisers, anti-bacterial
agents, and anti-allergenic compounds; for example if
there is a high pollen count within an enclosed space, in
20 order to prevent a person suffering from hay fever from
showing symptoms of their predicament. Other allergens
include fungal spores, dust mites (and their droppings),
pet allergens and the like, for example.

25 JP 2001 087370 discloses a deodoriser with spraying means
for neutralising acid and alkaline odour components when
detected by odour sensors.

It would therefore be advantageous to provide an active
30 ingredient release mechanism, which allows portions of air
treatment agent to be released from a device only as and
when a particular stimulus is present in the air space
around the device or within an enclosed space, and which

avoids ingredient release as the result of false detection of stimulus.

5 A problem with devices triggered by very low levels of airborne agent, such as may be detected by the human nose, is that such devices are prone to false detection and triggering, thus wasting the air treatment agent.

10 Another problem is that such devices may trigger when no humans are present, and so again the air treatment agent may be wasted.

15 It would also be advantageous to improve the efficiency of release of air treatment agents from devices, into airspaces, in particular maximising the distribution of the agent and enabling release in the optimum efficient manner in response to stimuli in the airspace, or lack of the stimuli. It would also be advantageous to provide an air treatment agent device which is not a line-of-sight
20 device, and which would not be triggered to release an air treatment agent by stimuli other than desired stimuli for said device.

25 It is the aim of preferred embodiments of the present invention to overcome or mitigate at least one problem of the prior art, whether expressly disclosed herein or not.

According to a first aspect of the invention there is provided an air treatment device comprising: an airborne
30 agent detector comprising a plurality of airborne agent sensors, wherein the airborne agent detector comprises means to detect a threshold level or concentration of an airborne agent; a means to mount a source of air treatment

agent to the device; and a means to expel a portion of air treatment agent from a mounted source of agent, upon detection of an airborne agent by the detector.

- 5 Preferably the airborne agent detector is of a type whose electrical conductivity is altered, by exposure to the airborne agent.

10 Preferably the threshold level is at least 0.1 ppm by volume of air of the target airborne agent, more preferably 0.05 ppm, even more preferably 0.01ppm .

Preferably said source is a single source of a target airborne agent.

15

The device may be of a type in which air treatment agent is expelled only in response to the detection of an airborne agent.

- 20 The device may be of a type in which the expulsion of air treatment agent in response to the detection of an airborne agent is not the only way in which air treatment agent is expelled. For example air treatment agent may be passively emanated, and on detection of an airborne agent,
25 an additional portion of air treatment agent is expelled to supplement the background level of passively emanated airborne agent. This may be achieved by various means, for example by expelling a pulse of air treatment agent using a pumping device, or preferably by use of a fan
30 which accelerates the rate of release of the air treatment agent from the passive emanator. In another embodiment, a heater element in proximity to a diffusion wick may be

actuated in order to increase the emanation of the air treatment agent.

By airborne agent is meant an airborne chemical in the
5 form of a gas, vapour, solid or liquid particle or droplet.

Suitably the airborne agent detector is operably connected to the means to expel a pulse of air treatment agent, such that the portion of air treatment agent is triggered in
10 response to an airborne agent being detected by the detector.

The means to mount a source of air treatment agent to the device may comprise means to connect a receptacle to the
15 device, the receptacle comprising the air treatment agent. The means to mount a source of air treatment agent may comprise a clip, retaining member, catch, flange, bracket or other similar structure, capable of cooperating with an agent-filled receptacle, and more preferably capable of
20 releasably mounting the agent-filled receptacle.

The portion of air treatment agent may be a pulse of air treatment agent. The portion may be a single pulse. The portion may be a continuous stream of agent over a defined
25 time period, or a plurality of intermittent pulses or streams of agent over a time period which may be pre-determined or be controlled by the device itself and related to the detected level of airborne agent.

30 The device may be arranged to expel a background level of air treatment agent which may be continuous or intermittent, and the portion of air treatment agent may comprise a booster portion of agent expelled by the device

upon detection of an airborne agent by the detector. Thus, for example the device may utilise as an air treatment agent, a deodorant, which may be expelled continuously at a low level to provide constant deodorising action, and
5 upon detection of an airborne agent by the detector, the device may be effected to expel a booster portion of the deodorant to counteract the detected airborne agent. The device may then return to expelling a continuous background level of agent when the detector detects no
10 further airborne agent, or detects an airborne agent under a minimum threshold concentration.

The airborne agent detector may comprise means to detect a single airborne agent or a mixture of airborne agents. The
15 airborne agent detector may comprise means for a user to input which airborne agent or agents the detector is arranged to detect, in use.

The airborne agent detector may comprise means to detect a
20 threshold level of an airborne agent or agents. The expulsion means may only be activated upon detection of the defined threshold, such as a threshold concentration, of an airborne agent, which threshold may be user set or factory set, for example. Thus, only upon detecting said
25 threshold, the detector may operably cooperate with the means to expel a portion of the air treatment agent from the device to activate expulsion of a portion of the air treatment agent.

30 The expulsion means may continue to expel the portion or a plurality of portions of air treatment agent, until the detector no longer detects an airborne agent or a threshold level of airborne agent.

The dose of air treatment agent expelled is preferably related to the detected level of airborne agent. For instance the dose of air treatment agent released may be proportional to the level of airborne agent detected. For instance the time over which expulsion of airborne agent takes place may be linked to the level of airborne agent detected.

10 Preferably the airborne agent detector is a gas detector. Thus, preferably the gas detector is arranged to detect a gas and effect expulsion of the portion of air treatment agent from the device in response to detection of the gas.

15 The gas detector may comprise one or more electronically conductive gas sensors and/or one or more semi-conductive gas sensors.

Preferably the detector comprises one or more semi-
20 conductive sensors.

The gas detector may comprise a plurality of sensors, each sensor comprising a different sensor material. Preferably the gas detector comprises at least 3 sensors, preferably
25 at least 4 sensors, each sensor comprising a different sensor material.

In one embodiment the airborne agent detector is adapted to detect sulphur-containing gases; preferably at least
30 one of hydrogen sulphide, methanethiol (also known as methyl mercaptan) and dimethyl sulphide; more preferably at least two of these; and most preferably all three.

In one embodiment the airborne agent detector is adapted to detect nitrogen-containing gases, preferably at least one of ammonia and nitrogen dioxide, preferably both of these.

5

In one embodiment the airborne agent detector is adapted to detect carbon monoxide.

The airborne agent detector may be adapted to detect at
10 least two, and preferably all three, of sulfur-containing gases; nitrogen-containing gases; and carbon monoxide.

Useful as semiconductor gas sensors are those gas sensors comprising a metal oxide. Thus preferably the gas
15 detector comprises at least one metal oxide gas sensor, hereinafter referred to as "MOX" gas sensors.

Semi-conducting MOX sensors, heated to approximately 300°C in air are known to exhibit a strong sensitivity to traces
20 of reactive gases present in the air. The sensitivity is translated into resistance change due to loss or gain of electrons as a result of the target gas reacting with oxygen. The loss or gain of electrons can thus be measured and correlated to determine which gases are
25 present in the air. Thus the loss or gain of electrons can be measured quantitatively as the magnitude of change in electrical resistance, and thus correlates to the concentration of target gas present around the sensor.

30 Suitable MOX gas sensors include gas sensors comprising oxides of tungsten, tin, any suitable semi conducting metal oxides, such as those comprising zinc, titanium, chromium, cobalt, molybdenum and vanadium, for example.

Particularly preferred MOX gas sensors include sensors comprising one or more of the following metal oxides: SnO_2 , WO_3 , $\text{Cr}_{2-x}\text{Ti}_x\text{O}_{3+z}$ (where x is from 0.1 to 0.8 and z is determined by the level of vacancies in the material, which is non-stoichiometric: preferably x is from 0.1 to 0.3), TiO_2 , ZnO , MoO_3 and V_2O_5 . The chemical formulae are indicative, as would be known to those in the art, because of the non-stoichiometry of the oxides.

10 The gas detector may comprise at least one n-type MOX sensor and at least one p-type MOX sensor.

Suitably the MOX sensor comprises a porous film or layer. Since the change in electrical resistance in the sensing electrode is carried by a surface reaction, it is advantageous to maximise the surface area to intensify the response to gas.

Preferably the MOX sensor comprises a metal oxide material connected to a substrate or chip, more preferably an aluminium or silicon substrate or chip. The MOX material is preferably connected to an electrode material, such as platinum or tantalum or a mixture thereof, for example. The electrode material may be inter-digital with the MOX material or may be connected by any other suitable orientation or configuration. There may be an insulating layer on top of the substrate, such as, for example, an oxide layer of the silicon or aluminium substrate between said substrate and said MOX material.

30

The MOX sensor may also comprise a means for heating the sensor to a required temperature. The means for heating the sensor may comprise a metal member connected to the

MOX material and operably connected to a heating means, such as an electrical heating element. The metal member may comprise the same material on the electrode material, where present, and may thus be, for example, platinum or
5 tantalum. The MOX sensor may be heated, in use, to a temperature of at least 300°C.

In particularly preferred embodiments, the MOX sensor comprises a substrate, preferably Si or Al, an oxide layer
10 of the substrate material, a MOX layer comprising interdigital electrodes, a heating member comprising the electrode material and a temperature sensor.

The MOX sensor may comprise one or more additives to
15 increase the selectivity and/or sensitivity of the MOX material to a particular gas or gases. The additive may be a catalytic additive such as platinum, palladium, gold or titanium, or activated carbon filters, for example.

Particularly preferred sensors for detection of sulfur-containing airborne agents are SnO_2 with Platinum and $\text{Cr}_2\text{-}$
20 $\text{xTi}_\text{x}\text{O}_{3+\text{z}}$

The MOX sensors may comprise one or more protective coating layers arranged to prevent ablation or damage to
25 the MOX material, in use. The protective coating layer may comprise a membrane, a sintered metal, carbon filter and the like, but the protective coating should not prevent charge transfer on the MOX sensor surface so preferably does not cover the active sensor material.

30

The gas detector may comprise a conducting polymer (CP) sensor, as an alternative to, or in addition to a MOX sensor.

There are a number of potential advantages in using conducting polymers, over the other sensor technologies, for vapour and gas sensing. There is a far wider choice
5 of materials and hence functional groups with which the gas or vapour can interact, and the materials are often easier to process than inorganic materials, i.e. metal oxides.

10 Some conducting polymer sensors can operate at room temperature, which is a distinct advantage over the semiconductor sensing technique, as there is a low power requirement. They also show reversible characteristics at room temperature, this means that the recovery rate of the
15 sensors after exposure to target compounds is better than SAW (Surface Acoustic Wave) sensors. The electronic control of the sensor is far less complicated than both semiconductor, MOX and SAW (Surface Acoustic Wave) detection. The CP sensor is stable up to 40°C and 90%
20 humidity, which is the most significant advantage over the other sensing techniques. Conducting polymer sensors may comprise two gold microelectrodes with an insulating gap between them. The conducting polymer is grown electrochemically across the gap to form a sensor. The
25 conductivity of the polymer is altered by the presence of nucleophilic and electrophilic gases which results in a decrease and increase in the conductivity respectively. Therefore by following the resistance between the two microelectrodes the sensors can be used to sense gases and
30 vapours. The polymers may be doped with anions such as Cl^- and SO_4^{2-} which can alter the sensitivity and/or selectivity to different vapours.

Suitable polymers for use in CP sensors include polypyrrole, polyaniline, polythiophene, polypyrrolidone, polyacetylene, polyaraphenylene, polyphthalocyanine, carbon black (or other carbon polymers).

5

Other sensors that may be used in the gas detector include SAW (surface acoustic wave) sensors, electrochemical cells, optical gas sensors, GASFETS (Gas Field Effect Transistors) pellistors, fibre optic gas sensors, and the
10 like for example.

A gas detector is not a 'line-of-sight' detector and is not sensitive to location or orientation. Accordingly the device can be positioned in an out-of-the-way or
15 unobtrusive location without affecting its operation.

In order to prevent a 'false positive' detection of gas by a detector, in which a gas similar to that which is arranged to be detected would trigger a release of the
20 air-treatment agent, the gas detector may comprise a plurality of different gas sensors, each of which must preferably detect a specific gas before the air-treatment agent pulse can be released. The plurality of gas sensors may comprise sensors of different materials, each of which
25 may be arranged, to detect the same gas or different gases. Thus, for example the gas detector may comprise an array of metal oxide sensors of different materials, each of which produce a different signal in response to the same gas, and only when a defined combination of signals
30 is emitted by the plurality of detectors will the air treatment agent be released.

Alternatively or additionally some or all of the gas sensors may be arranged to detect different gases and the air treatment agent may only be released when a certain number or concentration of gases is detected.

5

Alternatively the airborne agent detector may comprise a biosensor or chemical sensor, arranged in use to detect an airborne agent which may be a gas, liquid (including a vapour) or particulate solid.

10

The biosensor or chemical sensor may be arranged to detect an airborne particle of biological material such as pollen, an allergenic protein, fungal spores, micro organisms, other proteins and the like, for example, or an
15 airborne chemical.

The device may comprise its own power source, such as one or more batteries, for example, or solar cells. Alternatively the device may comprise a plug or socket,
20 arranged in use to cooperate with a corresponding electrical plug or socket, of for example, a mains electricity supply.

Some detectors such as gas sensors, chemical sensors and
25 biosensors generally may have a low power requirement, and therefore a device of the invention using such detectors may be suitable as a portable device utilising an internal power source such as a battery, for example.

30 The device may include a processor unit which receives the signal(s) produced in response to the airborne agent(s), and determines whether air treatment agent is emitted.

The device may include a person sensor, for example an infra-red sensor (e.g. a PIR sensor). The processor unit may be programmed such that only when a person is present, is the air treatment agent emitted, and only then, in response to the sensing of a target airborne agent.

The processor may be programmed to cause release of air treatment agent only when a sulfur-containing compound is detected.

10

The processor may be programmed to cause release of air treatment agent only when a nitrogen-containing compound is detected.

15 The processor may be programmed to cause release of air treatment agent only when carbon monoxide is detected.

The processor may be programmed to cause release of airborne treatment agent when two, or preferably three, of a sulfur-containing compound, a nitrogen-containing compound and carbon monoxide is detected.

20 The processor may be programmed to cause release of airborne treatment agent only when a sulfur-containing compound is not detected (but when another airborne agent is present).

25 The processor may be programmed to cause release of airborne treatment agent only when a nitrogen-containing compound is not detected (but when another airborne agent is present, to cause the release of the airborne treatment agent).

30

The processor may be programmed to cause release of airborne treatment agent only when carbon monoxide is not detected (but when another airborne agent is present, to cause the release of the airborne treatment agent).

5

The processor may be programmed to cause release of airborne treatment agent only when two of said types of airborne agents are not detected (but when the other type of airborne agent is detected, to cause the release of the
10 airborne treatment agent).

The device may include a timer, such that when the or each detector or sensor detects an airborne agent, air treatment agent is dispensed as a continuous stream for
15 defined period of time, and/or dispensed in a defined number of intermittent pulses. Intermittent pulses may be at regular time intervals or irregular time intervals.

The airborne agent detector, or detectors may be provided
20 with a ASIC (Application Specific Integrated Circuit) circuit as the processor unit, to provide the necessary signals to the air treatment agent dispensing means, in order to activate said dispensing means.

25 The air treatment agent may be housed in any suitable receptacle, such as a canister, bottle or vial, for example. The receptacle may be a pressurised container such as an aerosol can for example, and may thus comprise, in addition to the air treatment agent, a pressurised gas,
30 preferably a hydrocarbon gas (or hydrocarbon which is a gas at ambient temperature and pressure) such as propane, butane, or pentane, for example, or a halocarbon gas, such as chlorofluorocarbon gases.

The receptacle may be detachably mountable to the device. Thus when the receptacle becomes empty of air treatment agent the receptacle may be removed and either refilled,
5 or another agent filled receptacle mounted on the device.

The air treatment agent expulsion means may comprise any suitable means, such as a pump or aerosol for example, as are known to those skilled in the art. The dispensing
10 means may include a nozzle. The nozzle may comprise an aperture, such as a circular or elliptical hole, or an elongate slot, for example. The nozzle may comprise a plurality of apertures, such as a spray head for example. The plurality of apertures may comprise a mesh.

15

The expulsion means may simply comprise a wick to enable evaporation of an air treatment agent from the device. Alternatively the expulsion means may comprise ultrasonic
expulsion means, nebulising means, electrostatic discharge
20 means and the like, for example.

The nozzle preferably enables the air treatment agent to be dispensed as a spray or fine mist, which may be effected by forcing the agent through a plurality of
25 restricted size apertures, or the like, for example.

The air treatment agent preferably comprises an agent capable of masking, neutralising or retarding malodour, or unwanted odour in an airspace around the device. The air
30 treatment agent may comprise a deodorant, an anti-bacterial agent, a sanitizing agent, a fragrance or a perfume, for example. The air treatment agent may comprise an anti-allergenic material, preferably arranged

to react with and/or neutralise an allergen detected by the airborne agent detector, in use.

The air treatment agent may comprise a solid in the form of granules or powder, but preferably comprises a liquid or gas, at ambient temperature and pressure. Preferably the air treatment agent comprises a liquid, which may be dispensed in the form of a fine spray or mist through a suitable nozzle. If the air treatment comprises a gas or liquid, it may comprise a gas or vapour capable of reacting with the airborne agent to be detected in order to neutralise any malodour associated with the airborne agent.

By gas detector we mean a detector capable of detecting a gas or vapour *per se*, and/or fine particulate solids or liquid droplets dispersed in gases or air.

The device may comprise a fan or similar means, operably connected to the air treatment agent dispensing means. The fan may comprise part of the means to expel a portion of air treatment. The fan is preferably arranged to activate immediately prior to and/or during activation of the dispensing means, in order to effect increased speed of expulsion of the air treatment agent from the device, and/or to increase the distribution of the agent in the airspace surrounding the device.

The fan is preferably operably connected to the airborne agent detector, such that, upon detection of the airborne agent by the detector, the fan is activated prior to or during activation of the expulsion means.

The device may comprise a heater, operably connected to the air treatment agent dispersing means. The heater may be arranged to activate immediately prior to and/or during activation of the air treatment agent expulsion means, in
5 order to effect heating of the portion of air treatment agent as it is expelled from the device. Thus the heater may be used to vaporise, or render more fluid, a portion of air treatment agent expelled from the device.

10 The heater may be arranged to heat the portion when said portion is within the device or agent receptacle; alternatively the heater may be arranged to heat the portion as it leaves the device. The heat may also serve to improve distribution of the air treatment agent through
15 convection and may activate the air treatment agent molecules, if the air treatment agent comprises a composition which can be activated by heat, or which effects increased efficacy on heating.

The device may include an alarm, operable when a gas is
20 sensed which is dangerous. For example the device may have an alarm triggered by a threshold level of carbon monoxide.

According to a second aspect of the invention there is
25 provided a device of the first aspect of the invention on which is mounted a source of air treatment agent.

According to a third aspect of the invention there is provided a method of treating an airspace with an air
30 treatment agent, the method comprising the steps of detecting an airborne agent in an airspace and activating expulsion of an air treatment agent into the airspace in response to detection of the airborne agent.

The method may comprise providing an airborne agent detector, a source of air treatment agent and a means to expel, a portion of air treatment agent means upon
5 detection of an airborne agent by the detector.

The method may comprise expelling a single portion of agent in response to detection of an airborne agent, or may comprise dispensing a plurality of portions
10 intermittently, whether at regular or irregular intervals. Alternatively the expulsion of agent may comprise expelling a continuous stream of agent for a defined time period upon detection of gas. The expulsion means may expel a continuous portion or intermittent portions of
15 agent for as long as the detector detects an airborne or a defined threshold level of an airborne agent, or for a shorter or longer period of time, for example.

The portion(s) may be dispensed as a pulse of agent from
20 the dispensing means.

For example, in the case of the detector detecting a gas produced by tobacco smoking, or a mixture of gases, the expulsion means may be effected to expel a single portion
25 of air treatment agent, or may be effected to expel a plurality of portions for a defined time period or for such a time as the detector continues to detect the gas or gases. In some embodiments the expulsion means may also be arranged to expel one or more portions of agent when
30 the gas detector signals that no more further gas has been detected.

Alternatively, the expulsion means may dispense the portion continuously over a defined period of time, which period of time may be predefined by a user, or may correspond to a time period shorter than, equal to or
5 longer than the time period during which the airborne agent detector detects an airborne agent or defined threshold level of an airborne agent.

Preferably the method comprises treating an airspace
10 within a room, whether domestically (such as a kitchen, living room, bathroom, bedroom, toilet, garage, basement, loft, etc) commercially, or industrially. The method may comprise treating an airspace within an object, whether a closed object or an open object. Suitable objects include
15 dishwashers, washing machines, dustbins and other waste receptacles, wardrobes, laundry baskets, bags, shoes, vehicle interiors, refrigerators, cupboards, toilets, sanitary bins, nappy containers, sharps bins, and the like for example.

20

The airborne agent detector, air treatment agent expulsion means, and source of air treatment agent may be as described for the first aspect of the invention.

25 According to a fourth aspect of the present invention there is provided the method of the third aspect using the device of the first or second aspect.

For better understanding of the invention and to exemplify
30 how embodiments of the same may be put into effect, the invention will now be described by way of example with reference to the accompanying drawings in which:

Figure 1 illustrates a schematic view of a dispenser in accordance with the invention;

Figure 2 illustrates a plan view of the MOX sensor of the device shown in figure 1;

Figure 3 illustrates a side sectional view of one of the MOX sensors of the MOX sensor array shown in Figure 2;

Figure 4 shows the results of an experiment using the device of Figures 1 to 3, including MOX gas sensors, in simulated domestic conditions to sense gases produced by tobacco smoking;

Figure 5 shows the results of a second experiment using the device of Figures 1 to 3, in simulated domestic conditions; and

Figures 6 to 8 show the results of further experiments, with sulfur-containing gases.

We refer firstly to Figure 1 which illustrates a side sectional schematic view of an air treatment dispensing device of the invention.

25

The device comprises a housing 4 on which is located an airborne agent detector in the form of a gas detector, comprising a gas sensor array 6. Within the housing 4 is located a source of air treatment agent in the form of a detachable canister 8 which comprises a liquid deodorant as an air treatment agent. The canister 8 is in electronic communication with the sensor array 6 via an electrical circuit 7. The canister 8 comprises an outlet

conduit 11, at the end of which opens to a nozzle 10 which comprises a plurality of apertures (not shown) which enable deodorant to exit the housing 4 as a fine spray or mist, when the device 2 is used. Situated within the nozzle 10 is a fan 14, through which the outlet conduit 11 extends. The fan 14 is arranged in use to be actuated upon expulsion of a portion of deodorant from the outlet conduit 12 into the nozzle 10, in order to that the expelled portion is forced through the apertures of the nozzle 10, in order to increase distribution of the fine spray of mist outside of the device 2.

We turn now to Figures 2 and 3, which illustrate a front view and side sectional view of the sensor array 6 of Figure 1. The sensor array 6 comprises a substrate 13 comprising a silicon base 14 as shown in Figure 3 on which is laid an insulating SiO_2 layer 16 as shown in Figure 3. On top of the SiO_2 layer are positioned four metal oxide (MOX) sensors 12, 12', 12'', 12'''. The four MOX sensors 12, 12', 12'', 12''' comprise materials 20: SnO_2 , SnO_2/Pt , SnO_2 and SnO_2/Pt respectively.

Each MOX sensor 12, 12', 12'', 12''' further comprises its own abutting underlayer portion of the silicon substrate 14 and SiO_2 layer 16, and two spaced apart platinum electrodes 18, 18', the span of which is bridged by the MOX sensor material 20. The electrodes are connected to a voltmeter 24 which can determine resistance across the sensor material of the sensors 12, 12', 12'' and 12''', via electrical wires 22.

Each of the MOX sensors 12, 12', 12'', 12''', is operably connected to a heating member in the form of a Ta/Pt

resistance layer connected to the sensor material 20 of the four sensor array 6 and which contacts each of the four MOX sensors.

- 5 Use of the device 2, will now be described with reference to figures 1 to 3 and figures 4 and 5.

It is known that semi-conducting MOX sensors heated to approximately 300°C in air, exhibit strong sensitivity to
10 traces of reactive gases present in the air. The measurement effect is commercially exploited for only a relatively few number of oxides due to the requirement for a unique combination of resistivity, magnitude of resistance change in a specific gas (sensitivity) and
15 humidity effects. Amongst the oxides which are used as MOX sensors are SnO₂, as used in the sensor array 6 of the device 2 described hereinabove. The SnO₂ sensors can be enhanced, selectivity wise and sensitivity wise by the use of catalytic additives, such as the Pt present in sensors
20 12' and 12''' of the device 6.

The resistance change induced by the sensors is caused by loss or gain of the surface electrons as a result of absorbed oxygen reacting with a target gas. If the oxide
25 is an n-type, there is either a donation (producing gas) or subtraction (oxidizing gas) of electrons from the conduction band within the material. The result is that n-type oxides increase their resistance when oxidizing gases such as NO₂, O₃ are present while reducing gases
30 such as CO, CH₄, and ethanol lead to a reduction in the resistance. The converse is true for p-type oxides, where electron exchange due to gas interaction leads either to a rise (oxidizing gas) or a reduction (reducing gas) in

electron holes in the valence band. Each of these reactions then translates into corresponding changes in electrical resistance. Unlike some of the gas sensing technologies, MOX sensors can be made quantative, as the
5 magnitude of change in electrical resistance is a direct measure of the concentration of the target gas present.

The sensors 12, 12', 12'', 12''', were selected due to their advantageous properties in detecting NO₂, O₃, CO, CH₄
10 and ethanol, as are commonly produced as gases through smoking tobacco. Thus the device 6 which utilizes the sensor materials given above is particularly suited to sensing gases produced in tobacco smoking in a confined or semi-confined airspace.

15 Since the change in electrical resistance in the sensing oxide of sensors 12, 12', 12'' and 12''' is caused by surface reaction, it is advantageous to maximize the surface area to intensify the response to the gas. For
20 this reason, the sensors 12, 12', 12'' and 12''' include a layer of MOX material 20 which is in the form of a thin film. Alternatively the layer 20 may be slightly thicker, but highly porous. The MOX material 20 is either printed down or deposited onto the semi-conductive layer 16. The
25 electrodes 18, 18' are coplanar and located at the MOX material 20/semiconductor layer 16 interface. In the sensor array 6 shown in figure 2, the SiO₂ insulating layer 16 is approximately 1 μ m thick. The Ta/Pt inter-digital electrodes 18, 18' are approximately 200nm thick
30 but may be anywhere between 10nm and 1000nm thick.

Selectivity can be enhanced further if desired through the use of different metal oxide layers 20 in each of the

sensors, or use of catalytic additives, different operation temperatures, protective coatings and activated carbon filters, for example.

5 Upon detection by the sensors 12, 12', 12'' and 12''', and upon lowering of the resistance as shown in Figure 4, the sensor array 6 emits a signal via electrical circuit 7 to the canister 8 to effect dispensing of a portion of the deodorizing agent within the canister. Upon receipt of
10 the signal, a pump (not shown) within the canister 8 actuates to pump a portion of the deodorizing agent through the outlet conduit 11 and through the nozzle 10 of the device 2. As the canister 8 pumps out the portion of a treatment agent, the fan 14 is actuated. Thus as the
15 agent enters the nozzle 10, the fan effects increased dispersion of the agent from the nozzle 10 through the apertures (not shown), such that the spray or mist of the treatment agent reaches further into the airspace in which the device 2 is situated.

20

In use the air treatment device 2 is located within an airspace to be treated, such as a room, refrigerator, sanitary bin, sharps bin or the like etc.

25 Use of the device 2 will now be described by way of an experimental example. The device 2 was utilized in a living a room of a two person household, where tobacco smoking took place.

30 The device 2 was mounted to a wall within the living room of a household in Hessle, UK, and activated to detect a combination of gases produced in combustion of tobacco through persons in the room smoking cigarettes.

In particular, the sensor material 20 of the sensors 12, 12', 12'', 12''' of the device 6 are able to detect NO₂, O₃, CO, CH₄ and ethanol, which are common gases produced
5 through combustion of tobacco.

The device 6 was activated, and a person entered the room at a predetermined time 9.30am, and lit a cigarette. Approximately 2½ hours later a second cigarette was lit
10 within the room by the same person. Figure 4 shows the output results of the four sensors 12, 12', 12'', and 12''', in response to detection of gases produced by the cigarette smoke within the airspace. As can be seen from Figure 4, as the first cigarette was lit at 9.30am, the
15 sensors 12, 12', 12'' and 12''' recorded a decreasing resistance across the sensor material 20. When the second cigarette was lit at 1.10pm, again the four sensors 12, 12', 12'' and 12''' recorded a decrease in resistance across the sensing material 20.

20

Upon detection by the sensors 12, 12', 12'' and 12''', and upon lowering of the resistance as shown in Figure 4, the sensor array 6 emitted a signal via electrical circuit 7 to the canister 8 to effect dispensing of a portion of the
25 deodorizing agent within the canister. Upon receipt of the signal, a pump (not shown) within the canister 8 actuated to pump a portion of the deodorizing agent through the outlet conduit 11 and through the nozzle 10 of the device 2. As the canister 8 pumped out the portion of
30 a treatment agent, the fan 14 was actuated. Thus as the agent entered the nozzle 10, the fan effected increased dispersion of the agent from the nozzle 10 through the apertures (not shown), such that the spray or mist of the

treatment agent reached further into the living room in which the device 2 was situated.

Figure 5 shows the results of a second experiment in which the device 6 was placed in a second living room at a household in Freiburg, Germany. Three cigarettes were smoked during the day at 11.10am, 11.45am and 7.25pm. The device 2, for this experiment, was utilised with only two sensors, 12 and 12', corresponding to the SnO_2/Pt and SnO_2 materials as sensor material 20. It can be seen that immediately upon lighting a cigarette at 11.10am, 11.45am and 7.25pm resistance was lowered across the MOX material 20 of the sensors 12 and 12', which induced a signal, which was subsequently emitted via the control circuit 7 to the canister 8. The canister 8 then actuated release of a portion of deodorizing air treatment agent out of the device 2 via the nozzle 10 as described herein before, in order to mask the tobacco gas malodour.

Thus the device 2 can be used effectively to counter malodour produced by tobacco smoking or other malodour produced within a confined airspace. Sensor 2 may be situated in any confined or semi-confined airspace where malodours occur. The sensor material 20 may be changed to increase selectivity and/or sensitivity to varying gases which may be produced as part of a malodour.

In alternative embodiments, instead of MOX sensor material, conducting polymer (CP) sensors may be utilised. There are a number of potential advantages in using conducting polymers, over the other sensor technologies, for vapour sensing. There is a far wider choice of materials and hence functional groups with which the

vapour can interact, and the materials are often easier to process than inorganic materials, i.e. metal oxides. Some conducting polymer sensors can operate at room temperature, which is a distinct advantage over the semiconductor MOX sensing technique, as there is an inherent low power requirement. They also show reversible characteristics at room temperature, this means that the recovery rate of the sensors after exposure to target compounds is better than SAW (Surface Acoustic Wave) sensors. The electronic control of the sensor is far less complicated than both semiconductor MOX and SAW detection. The CP sensor is stable up to 40°C and 90% humidity, which is the most significant advantage over the sensing techniques.

The conducting polymer sensors are essentially two gold microelectrodes with an insulating gap between them. The conducting polymer is grown electrochemically across the gap to form the sensor. The conductivity of the polymer is altered by the presence of nucleophilic and electrophilic gases which results in a decrease and increase in conductivity respectively. Therefore by following the resistance between the two microelectrodes the sensors can be used to sense gases and vapours. The polymers may be doped with anions such as Cl^- and SO_4^{2-} , which can alter the sensitivity to different vapours.

The conducting polymer, once coated onto the electrode material, requires activation before use as a chemical sensor. Activation is required to convert the insulating, neutral form of the polymer to oxidized, positively charged, conducting form where anions from an electrolyte solution are incorporated into the polymer film. To

- achieve this the polymer films are first characterized in a base electrolyte by another electrochemical process called cyclic voltammetry. Here the potential is cycled between certain limits at a chosen scan rate for at least two complete cycles. The point at which an oxidation peak occurs gives the maximum potential required for activation, and potentials above this which cause over oxidation and degradation of the conducting polymer film.
- 10 Other gas detectors that may be used alternatively or additionally to MOX and CP based gas detectors include those comprising Surface Acoustic Wave sensors and/or sensor materials.
- 15 In further embodiments the portion of dispensing agent dispensed upon detection of a gas or plurality of gases by the sensor array 6 may comprise a plurality of intermittent pulses, whether at regular or irregular time intervals, or may comprise a continuous dispersal of a stream of air treatment agent over a defined period of time. The defined period of time may be user defined or preset in the device 2. The device 2 may emit a constant background level of air treatment agent and expel a portion, in the form of a booster portion upon detecting an airborne agent in an airspace.
- 20
- 25

The device 2 may include a heater, in other embodiments, in addition to or alternative to the fan 14. The heater may be arranged to render any air treatment agent expelled through the nozzle 10 more fluid or vaporize a liquid air treatment agent. The heater may even activate air treatment agents which comprise heat-activated compounds. Other air treatment agent expulsion means may include

30

nebulisers, electrostatic means, a simple wick or the like for example.

In yet further alternative embodiments the portion of air treatment agent to be dispensed may be effected to be dispensed immediately upon detection of a gas, or at any defined time interval after detection of a gas. The fan 14 may be effected to continue operation after the portion of air treatment agent has been dispensed, in order to further encourage the air treatment agent to disperse around the airspace after the device 2 has been activated.

The device 2, may comprise, instead of a gas detector, a detector in the form of a biosensor or chemical sensor. The biosensor or chemical sensor may be arranged to detect a particulate solid, liquid or gas in air, and may be arranged to detect chemical agents or biological material such as proteins, microorganisms, allergens, fungal spores and the like for example. The biosensor or chemical sensor may be any suitable sensor such as an amperometric sensor, optical sensor, or the like, for example, as are well known to those skilled in the art.

Further experiments were carried out with a device comprising four sensors, namely: SnO_2 ; $[\text{SnO}_2+\text{Pt}]$ (in series); CTO ($\text{Cr}_{1.8}\text{Ti}_{0.2}\text{O}_{3+z}$); and WO_3 . All were set on a common silicon wafer, on a common quartz substrate.

The target gases were H_2S , $(\text{CH}_3)_2\text{S}$ and CH_4S . The tests were carried out under ambient conditions, with the usual heating of the sensors.

Fig. 6 shows the change in resistance across the CTO, SnO_2 and $[\text{SnO}_2+\text{Pt}]$ sensors (R = resistance; R_o = original resistance) at concentrations of 2 ppm, 5 ppm and 10 ppm of $(\text{CH}_3)_2\text{S}$. The CTO and $[\text{SnO}_2+\text{Pt}]$ sensors appear to be particularly discriminating.

Fig. 7 shows corresponding results for CH_4S at concentrations of 0.1 ppm, 0.2 ppm, 0.5 ppm and 1 ppm by volume. In the case of this gas the CTO and SnO_2 sensors appear particularly discriminating.

Fig. 8 shows corresponding results for H_2S at concentrations of 0.1 ppm, 0.2 ppm, 0.5 ppm and 1 ppm by volume. In the case of this gas, all the sensors tested appeared to be discriminating.

Tests were also carried out on the unit for which results are given in Figs. 6 to 8, but using CO , NO_2 and NH_3 , in turn, as the gas. These are regarded in this example only as interfering or rogue gases in the context of detecting the target gases; it is not wished that they trigger release of airborne agent in this example. It was found that they gave a small change in sensor resistance at normal levels; such that they would not release of airborne agent. If necessary a sensor "tuned" to CO , NO_2 or NH_3 could be provided, such that if that sensor fired, the device either would not trigger the release of airborne agent, or would only do so if an especially high level of H_2S , CH_4S or $(\text{CH}_3)_2\text{S}$ was detected.

Claims

1. An air treatment device comprising: an airborne agent
5 detector comprising a plurality of airborne agent
sensors, wherein the airborne agent detector comprises
means to detect a threshold level or concentration of
an airborne agent; a means to mount a source of air
treatment agent to the device; and a means to expel a
10 portion of air treatment agent from a mounted source
of agent, upon detection of an airborne agent by the
detector.
2. An air treatment device according to claim 1 wherein
15 the mounted source of air treatment agent also
passively emanates the air treatment agent.
3. An air treatment device as claimed in Claim 1 or Claim
2, wherein the means to mount a source of air
20 treatment agent to the device comprises means to
connect a receptacle to the device, the receptacle
comprising the air treatment agent.
4. An air treatment device as claimed in any preceding
25 claim, wherein the device includes a processor unit to
determine whether the signals from the sensors cause
expulsion of a portion of air treatment agent.
5. An air treatment device as claimed in any preceding
30 claim, wherein at least two sensors sense the same
airborne agent and the processor unit must receive
signals from both sensors in order to cause a portion
of airborne treatment agent to be expelled.

6. An air treatment device as claimed in claim 4 or 5,
wherein the detector includes a sensor which detects
both a target airborne agent and a non-target airborne
agent, wherein in order to eliminate expulsion of air
treatment agent in response to the non-target agent,
the device includes a second sensor which detects the
non-target air treatment agent but not the target air
treatment agent, the processor unit being arranged to
prevent expulsion of the air treatment agent when the
second sensor detects a signal, completely or until
the first sensor gives a signal at a higher threshold
value than usual.
7. An air treatment device as claimed in claim 4, 5 or 6,
wherein the detector includes a person detector (e.g.
a PIR), and the processor unit allows airborne
treatment agent to be expelled, in response to a
signal from one or more of the sensors, only when the
person detector gives a signal and for an interval
thereafter.
8. An air treatment device as claimed in any preceding
claim, wherein the airborne agent detector is a gas
detector.
9. An air treatment device as claimed in any preceding
claim, wherein the detector comprises one or more
electronically conductive gas sensors and/or one or
more semi-conductive gas sensors.

10. An air treatment device as claimed in any preceding claim, wherein the detector comprises a conducting polymer sensor.
- 5 11. An air treatment device as claimed in any preceding claim, wherein the air treatment agent expulsion means comprises a pump or aerosol.
- 10 12. An air treatment device as claimed in any preceding claim, on which is mounted a source of air treatment agent.
- 15 13. An air treatment device as claimed in any preceding claim, wherein the air treatment agent comprises an agent capable of masking, neutralising or retarding malodour, or unwanted odour.
- 20 14. An air treatment device as claimed in any preceding claim, wherein the air treatment agent comprises a deodorant, an anti-bacterial agent, a sanitizing agent, a fragrance, a perfume or an anti-allergenic agent.
- 25 15. A method of treating an airspace with an air treatment agent, the method comprising the steps of detecting an airborne agent in an airspace and activating expulsion of an air treatment agent into the airspace in response to detection of the airborne agent.
- 30 16. A method as claimed in Claim 15, comprising the step of expelling a single portion of agent in response to detection of an airborne agent, or a plurality of portions intermittently.

17. A method as claimed in Claim 15, wherein expulsion of
an agent comprises expelling a continuous stream of
agent for a defined period of time upon detection of
an airborne agent.
18. A method as claimed in any one of Claims 15 to 17,
using the device of any one of Claims 1 to 14.
19. An air treatment device substantially as described
herein with reference to the accompanying drawings.
20. A method substantially as described herein with
reference to the accompanying drawings.

1/4

Fig.1.





Fig.2.



2/4

Fig.3.





Fig.4.



3/4

Fig.5.





Fig.6.



4/4

Fig.7.





Fig.8.



INTERNATIONAL SEARCH REPORT

GB2004/003485

A. CLASSIFICATION OF SUBJECT MATTER
IPC 7 A61L9/12

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 7 A61L G01N

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the International search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 21, 3 August 2001 (2001-08-03) -& JP 2001 087370 A (DENSO CORP), 3 April 2001 (2001-04-03) cited in the application abstract	1-4, 8, 9, 11-16, 18-20
Y		6, 10
X	PATENT ABSTRACTS OF JAPAN vol. 2000, no. 07, 29 September 2000 (2000-09-29) -& JP 2000 121110 A (ELMO CO LTD), 28 April 2000 (2000-04-28) abstract -/--	1-4, 8, 9, 11-20

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

- *T* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- *X* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- *Y* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- *&* document member of the same patent family

Date of the actual completion of the international search

14 October 2004

Date of mailing of the international search report

21/10/2004

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

Marti, P

INTERNATIONAL SEARCH REPORT

GB2004/003485

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	-& DATABASE WPI Derwent Publications Ltd., London, GB; AN 2000-402951 XP002299934 -& JP 2000 121110 A (ELMO CO LTD) 28 April 2000 (2000-04-28) abstract -----	
X	DE 101 57 832 A (KRUSE EIKE) 26 June 2003 (2003-06-26) the whole document -----	1-4,7-9, 11-20
X	FR 2 689 399 A (GENE DIDIER ; MARTIN JOAQUIM) 8 October 1993 (1993-10-08) ----- page 2, line 1 - line 22 page 3, line 24 - page 5, line 2 -----	1-4,8,9, 11-16, 18-20
P,X	DE 102 49 510 A (BEHR GMBH & CO) 6 May 2004 (2004-05-06) ----- paragraph '0020! - paragraph '0021!; figures 1,2 -----	1-4,8,9, 11-16, 18-20
P,X	WO 2004/062700 A (FREUDENBERG CARL KG ; KLATT CHRISTOPHER (DE); BORRIS RICHARD (DE); REI) 29 July 2004 (2004-07-29) page 9 - page 13 -----	1-4, 11-16, 18-20
P,X	PATENT ABSTRACTS OF JAPAN vol. 2003, no. 12, 5 December 2003 (2003-12-05) -& JP 2004 141618 A (TOTO LTD), 20 May 2004 (2004-05-20) abstract -----	1-4,7-9, 11-16, 18-20
P,X	-& DATABASE WPI Derwent Publications Ltd., London, GB; AN 2004-395768 XP002299935 -& JP 2004 141618 A (TOTO LTD) 20 May 2004 (2004-05-20) abstract -----	1-4,7-9, 11-16, 18-20
X	PATENT ABSTRACTS OF JAPAN vol. 018, no. 032 (C-1154), 18 January 1994 (1994-01-18) -& JP 05 261246 A (TOTO LTD), 12 October 1993 (1993-10-12) abstract ----- -/--	1,4,5,8, 9,13-15

INTERNATIONAL SEARCH REPORT

3B2004/003485

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
	<p>-& DATABASE WPI Derwent Publications Ltd., London, GB; AN 1993-356533 XP002299936 -& JP 05 261246 A (TOTO LTD) 12 October 1993 (1993-10-12) abstract</p> <p>-----</p>	
X	<p>PATENT ABSTRACTS OF JAPAN vol. 017, no. 288 (M-1423), 3 June 1993 (1993-06-03) -& JP 05 016660 A (ZEXEL CORP), 26 January 1993 (1993-01-26) abstract</p> <p>-----</p>	1,5,15
Y	<p>PATENT ABSTRACTS OF JAPAN vol. 016, no. 036 (M-1205), 29 January 1992 (1992-01-29) & JP 03 244957 A (SEIBU GAS KK; others: 01), 31 October 1991 (1991-10-31) abstract</p> <p>-----</p>	6
Y	<p>WO 96/30750 A (CALIFORNIA INST OF TECHN) 3 October 1996 (1996-10-03) page 3, line 8 - line 21 page 15, line 13 - page 16, line 10</p> <p>-----</p>	10

INTERNATIONAL SEARCH REPORT

Information on patent family members

GB2004/003485

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
JP 2001087370	A	03-04-2001	NONE	
JP 2000121110	A	28-04-2000	NONE	
DE 10157832	A	26-06-2003	DE 10157832 A1	26-06-2003
FR 2689399	A	08-10-1993	FR 2689399 A1	08-10-1993
DE 10249510	A	06-05-2004	DE 10249510 A1 WO 2004037304 A1	06-05-2004 06-05-2004
WO 2004062700	A	29-07-2004	DE 10301214 B3 WO 2004062700 A1	15-04-2004 29-07-2004
JP 2004141618	A	20-05-2004	NONE	
JP 05261246	A	12-10-1993	JP 3087432 B2	11-09-2000
JP 5261246	A	12-10-1993	JP 3087432 B2	11-09-2000
JP 05016660	A	26-01-1993	JP 2855294 B2	10-02-1999
JP 03244957	A	31-10-1991	NONE	
WO 9630750	A	03-10-1996	US 5571401 A AT 188291 T AU 705825 B2 AU 5372896 A CA 2215332 A1 CN 1184530 A DE 69605906 D1 DE 69605906 T2 DK 820585 T3 EP 0820585 A1 EP 0950895 A2 ES 2144737 T3 FI 973802 A GR 3033092 T3 JP 11503231 T PT 820585 T RU 2145081 C1 US 5951846 A US 5959191 A US 6013229 A WO 9630750 A1 US 5891398 A US 6170318 B1 US 6017440 A US 6093308 A US 2003159927 A1 US 6537498 B1 US 2004033165 A1 US 6331244 B1 US 5698089 A US 5788833 A US 6010616 A	05-11-1996 15-01-2000 03-06-1999 16-10-1996 03-10-1996 10-06-1998 03-02-2000 13-07-2000 19-06-2000 28-01-1998 20-10-1999 16-06-2000 29-09-1997 31-08-2000 23-03-1999 30-06-2000 27-01-2000 14-09-1999 28-09-1999 11-01-2000 03-10-1996 06-04-1999 09-01-2001 25-01-2000 25-07-2000 28-08-2003 25-03-2003 19-02-2004 18-12-2001 16-12-1997 04-08-1998 04-01-2000